


SPECIFICATION FOR APPROVAL

Multilayer Ceramic Chip Capacitors								
Customer :								
Capacitance : 3.3 uF		Tolerance : ±10 %		Issue No.				
Temp. Coef. X5R		Q'ty of Sample : pcs		Issue Day. 24/02/2022				
Size: 0805		Part No. 0805X335K160N3		W.V. 16 VDC				
Diagram of Dimensions : (Unit : mm)								
			L: <u>2.00 ±0.20</u> W: <u>1.25 ±0.20</u> T: <u>1.25 ±0.20</u> t: <u>0.50 ±0.20</u>					
SPECIFICATION				Initial Test				
				No	uF	D.F.	I.R.	T.V.
Frequency = 1K Hz Temperature = 25°C				1.				
1	Operating Temperature Range : -55°C ~ +85°C			2.				
2	Dissipation Factor : 10 % Max.			3.				
3	Insulation Resistance : 10 GΩ Min.			4.				
4	Dielectric Strength Test : DC 40 V			5.				
5	Temperature Characteristics : ±15% at -55°C to +85°C			6.				
				7.				
				8.				
				9.				
				10.				
APPROVED BY CUSTOMER				REMARK :				
Your Confirmation : ☐ Approval ☐ Conditional Approval ☐ Rejection (Please send a copy for our ref.)				Spec. Applied by EIA RS 198. JIS 5102. IEC 384-10 Test Instruments: (1). Capacitance: HP 4278A L.C.R.METER (2). Dissipation Factor: as the Item (1). (3). Insulation Resistance: CHEN HWA 705 (4). Dielectric Strength: CHEN HWA 203				
Inspected by		Checked by		吳美華		Approved by		許介洲