


SPECIFICATION FOR APPROVAL

Multilayer Ceramic Chip Capacitors							
Customer :							
Capacitance : 22 nF	Tolerance : ±10 %		Issue No.				
Temp. Coef. X7R	Q'ty of Sample : pcs		Issue Day. 27/01/2021				
Size: 1206	Part No. 1206B223K101NT		W V 100 VDC				
Diagram of Dimensions : (Unit : mm)							
			L: <u>3.20 ±0.20</u> W: <u>1.60 ±0.20</u> T: <u>0.85 ±0.10</u> t: <u>0.30 ~ 0.70</u>				
SPECIFICATION			Initial Test				
			No	nF	D.F.	I.R.	T.V.
Frequency = 1K Hz Temperature = 25°C			1.				
1	Operating Temperature Range : -55°C ~ +125°C		2.				
2	Dissipation Factor : 2.5 % Max.		3.				
3	Insulation Resistance : 10 GΩ Min.		4.				
4	Dielectric Strength Test : DC 250 V		5.				
5	Temperature Characteristics : ±15% at -55°C to +125°C		6.				
6	For further details please visit the following link of our website:		7.				
	MLCC-Approval_20200916.pdf		8.				
			9.				
			10.				
APPROVED BY CUSTOMER			REMARK :				
Your Confirmation : <input type="checkbox"/> Approval <input type="checkbox"/> Conditional Approval <input type="checkbox"/> Rejection (Please send a copy for our ref.)			Spec. Applied by EIA RS 198. JIS 5102. IEC 384-10 Test Instruments: (1). Capacitance: HP 4278A L.C.R.METER (2). Dissipation Factor: as the Item (1). (3). Insulation Resistance: CHEN HWA 705 (4).Dielectric Strength: CHEN HWA 203				
Inspected by		Checked by	吳美華	Approved by	許介洲		