





# Hubei Kento Electronic Co., Ltd

## Specification for LED Product

### 3AG4HC01

Package Dimensions(mm)



Notes:

All dimension units are millimeters.

All dimension tolerance is  $\pm 0.2\text{mm}$  unless otherwise note



An epoxy meniscus may extend about 1.5mm down the leads.

Burr around bottom of epoxy may be 0.5mm max.

Synopsis:            3mm Round Type  
                          Green LED Lamp

Water Clear Lens



## Hubei Kento Electronic Co., Ltd

<b>3AG4HC01</b>						
Typical Electrical & Optical Characteristics (Ta = 25°)						
ITEMS	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	VF	IF = 20mA	1.6	2.1	2.65	V
Reverse Current	IR	VR = 5V	---	---	1.1	μA
Dominant Wavelength	λ D	IF = 20mA	570	---	574	nm
Luminous Intensity	IV	IF = 20mA	82	111	126	mcd
50% Power Viewing Angle	2θ½	IF = 20mA	---	40	---	deg
Absolute Maximum Ratings at (Ta = 25°)						
ITEMS	SYMBOL	ABSOLUTE MAXIMUM RATING				UNIT
Forward Current	IF	50				mA
Peak Forward Current	IFP	220				mA
Continuous Forward Current	IL	20				mA
Reverse Voltage	VR	5				V
Power Dissipation	PD	105				mW
Operation Temperature	Topr	-40 ~ +80				°C
Storage Temperature	Tstg	-40 ~ +80				°C
Lead Soldering Temperature	Tsol	Max.260°C for 5 sec Max.				

IFP Conditions Pulse Width 10msec duty 1/10


Tsol Conditions 4mm from the base of the epoxy bulb



## Hubei Kento Electronic Co., Ltd

### 3AG4HC01

Spatial Distribution



Reliability Performance


Test Classification	Test Item	Test Conditions	Test Duration	Sample Size	Standard
Life Test	Life Test	Ta=25°±5 IF=20mA	1000 hrs	10PCS	
Environment Test	Thermal Shock Test	-10°±5°←→+100°±5° 5min. 10sec. 5min.	100 cycles	10PCS	
	Temperature Cycle Test	55°C±5°C←→+85°C±5° 30min. 5min. 30min.	100 cycles	10PCS	
	High Temperature C High Humidity Test	Ta=85°±5% RH =85%±0.5 %RH	240 hrs	10PCS	
	High Temperature Storage	Ta=100°±5%	1000 hrs	10PCS	
	Low Temperature Storage	Ta=-55°±5%	1000 hrs	10PCS	
Mechanical Test	Resistance to Soldering Heat	Ta=260°±5%	5 sec.	10PCS	
	Lead Integrity	0° ~ 90° ~ 0°	3 times	10PCS	




# Hubei Kento Electronic Co., Ltd

## 3AG4HC01

Typical Optical/Electrical Characteristics Curves (Ta=25° Unless Otherwise Noted)



Current-Voltage Curve



Current-Luminous intensity Curve





Current-Luminous flux Curve



# Hubei Kento Electronic Co., Ltd

## 3AG4HC01



Wavelength

