

Model:		
<div style="border: 1px solid black; border-radius: 15px; width: 100px; height: 50px; background-color: #00A0C0; color: white; display: flex; align-items: center; justify-content: center; margin: 10px auto;"> D2-R </div>		*2MP Wall lamp Camera (excluding TF Card) X 1 * Specification X1 * Screw pack X1
Packing box size(mm)/weight(kg)		164*128*88mm/0.32kg
Outer box size(mm)/weight(kg)		545x345x470mm/14kg/40PCS
Specification parameter		
system	Main Processor	Dual-core 32-bit DSP (XM530), pure hard compression, watchdog
	image sensor	2MP 1/2.9" SC2235P high-performance CMOS sensor
	Operation System	Embedded LINUX OS system
	Video Compression	Smart H.265X
	APP	ICSEE(support andriod and IOS)
Video	High Definition	1080P
	Image resolution	1920*1080
	Minimum illumination	0.1LUX/F1.2
	Lens	3.6mm
	Perspective	92°
	Turn video	Upside down/Turn around
lighting	Light control mode	Full Color/Smart/Infrared Night Vision
	Number of lights	16 infrared lamps +32 white lamps
PTZ	PTZ control	Does not support
	Turn PTZ	Does not support
Audio	Coding standard	G.711
	Mitou	Support
	Two-way Speech	Support
Record management	Video file size	≈4G/day
	Record Mode	Manual record, motion detection record, scheduled record, alarm
	Video storage	TF Card/Cloud
	storage	support TF card (max 128GB) or cloud storage
	Remote playback	Support
	Image capture	Support
Network	WIFI	2.4G WIFI 802.11b/g/n
	Pairing	Sweep QR code, Network Cable connection, AP Hotspot Addition
	Network Protocol	Support TCP/IP, ONVIF, RTSP
extension	Reset key	Support
	Human tracking	Does not support
	360degree coordinate positioning	Does not support
power supply	Power	DC 12V
	power interfac	DC 5521 interfac
work environment	Suitable place	outdoor、Home、shop、School、factory;
	Installation mode	Wall hanging
	Working Temperature	-20℃ — +55℃
	Working humidity	10% — 90%

