

产品规格书

Product Specification



DFHY3.6KW



Built-in 100A
Solar Charger



Wide MPPT
Range 40-500V



Workable with
Generator



Complete CE
Certificate



Lithium Battery
Activation




Detachable
Dust Cover



WiFi
Monitoring

System Diagram



Specifications

Model	DFHY3.6KW
AC Input	
Rated Input Voltage (VAC)	208/220/230/240;L+N+PE
Voltage Range (VAC)	90~280±3(normal mode):170~280±3(UPS mode)
Frequency(Hz)	50/60(Auto Adaptive)
AC Output	
Rated Capacity (kW)	4.0
Surge Power (kVA)	5.7
Voltage (VAC)	208/220/230/240
Power Factor(PF)	1
Frequency	50/60Hz±0.1%
Switch Time (ms)	10(normal mode)/10 (UPS mode)
Wave Form	Pure Sine Wave
Overload Capacity (Battery Mode)	60s@102%~110% load; 10s@110%~130% load; 3s@130%~150% load; 0.2s@>150% load
Max. Efficiency (Battery Mode)	92.7%@24VDC
Parallel Quantity	NA
Charger (PV / AC)	
Solar Charger Type	MPPT
Max PV input Current/Input Power	18A/5000W
MPPT Range@Operating Voltage (VDC)	40~450
Max PV Open Circuit Voltage (VDC)	500
Max PV Charge Current (A)	100
Max AC Charge Current (A)	100
Max. Charge Current (PV + AC)(A)	100
Battery	
Rated Voltage(VDC)	24
Floating Charge Voltage (VDC)	27
Overcharge Protection (VDC)	30.5
Battery Type	Lithium and Lead-acid
Interface	
HMI	LCD
Interface	RS485/RS232/USB /Dry Contact
Monitoring	WiFi (Optional)
General Data	
Ingress Protection	IP20
Operating Temperature	-10℃~ 50℃
Relative Humidity	5%~95%(Non-condensing)
Storage Temperature	-15 ℃~ 60 ℃
Net Weight (kg)	6.25
Dimensions(W*H*D)	440*290*100mm(without bracket)
Max. Operating Altitude	4000m(Derating above 1000m)