

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、商业秘密等权利外，本公司保留对涉及发明、实用新型、外观设计、软件著作权、集成电路布图设计专有权、商业秘密等权利的所有权利。

FOR-1755 Rev.1.7

2







3

4

5

6

PCB LAYOUT



Note:

The A&Z(H) in the name means: A(H) and Z(H).

5	Pin header	Copper	Sn plated
4	Button	PA66	UL94V-0
3	Spring	Stainless steel	/
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/8	/	300/8
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		/	200/10	/
工频耐压/Withstanding Voltage(V/Min)		AC2000		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)		20~16 / 0.2~1.5		
间距/Pitch(mm)/线数范围/Poles		3.81/N=02~24P		
剥线长度/Stripping length(mm)		8~9		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

			MATERIAL:		SURFACE/COLOR:		
			MAT NO. /REV:		MAT STATUS: 批量		
APPD: 兰春华			2022. 10. 19		NAME DG236-3. 81-XXP-1Y-00A&Z (H)		
CHKD: 陈招			2022. 10. 19				
DRFT: 龚徐涛			2022. 10. 18				
DRAWING NO.		TYPE		DRAWING STATUS		SCALE	SHEET
200029173		CUSTOMER DRAWING		已发布		2: 1	1/1
 A4		 (inch)					

00			龚徐涛	2022.10.18
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6