


# GBU6A - GBU6M

### **Features**

- Surge overload rating: 175 amperes peak.
- Reliable low cost construction utilizing molded plastic technique.
- Ideal for printed circuit board.





## 6.0 Ampere Bridge Rectifiers

### **Absolute Maximum Ratings\***

T<sub>A</sub> = 25°C unless otherwise noted

Symbol	Parameter	Value	Units		
lo	Average Rectified Current @ T <sub>A</sub> = 100°C	6.0	А		
İf(surge)	Peak Forward Surge Current 8.3 ms single half-sine-wave Superimposed on rated load (JEDEC method)	175	А		
P <sub>D</sub>	Total Device Dissipation  Derate above 25°C	14.5	W mW/°C		
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient,** per leg	8.6	°C/W		
$R_{\theta JC}$	Thermal Resistance, Junction to Case,*** per leg	3.1	°C/W		
T <sub>stg</sub>	Storage Temperature Range	-55 to +150	°C		
TJ	Operating Junction Temperature	-55 to +150	°C		

<sup>\*</sup>These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

### **Electrical Characteristics** T<sub>A</sub> = 25°C unless otherwise noted

Parameter	Device						Units	
	6A	6B	6D	6G	6J	6K	6M	
Peak Repetitive Reverse Voltage	50	100	200	400	600	800	1000	V
Maximum RMS Input Voltage	35	70	140	280	420	560	700	V
DC Reverse Voltage (Rated V <sub>R</sub> )	50	100	200	400	600	800	1000	V
Maximum Reverse Leakage, per element								
@ rated $V_R$ $T_A = 25^{\circ}C$		5.0						μΑ
$T_A = 125^{\circ}C$		500						μΑ
Maximum Forward Voltage Drop, per element								
@ 6.0 A				1.0				V
$I^2$ t rating for fusing $t < 8.35 \text{ ms}$	127					A <sup>2</sup> Sec		


<sup>\*\*</sup> Device mounted on PCB with 0.5 x 0.5" (12 x 12 mm).


<sup>\*\*\*</sup> Device mounted on Al plate with 2.6 x 1.4" x 0.06" (6,5 x 3.5 x 0.15 cm).


## **Bridge Rectifiers**


(continued)


## **Typical Characteristics**











### **TRADEMARKS**

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEX<sup>TM</sup> ISOPLANAR<sup>TM</sup>
CoolFET<sup>TM</sup> MICROWIRE<sup>TM</sup>

CROSSVOLT<sup>TM</sup> POP<sup>TM</sup>

E<sup>2</sup>CMOS<sup>™</sup> PowerTrench<sup>™</sup>

FACT<sup>TM</sup> QS<sup>TM</sup>

#### **DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

 A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### PRODUCT STATUS DEFINITIONS

#### **Definition of Terms**

Datasheet Identification	Product Status	Definition					
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.					
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.					
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.					
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.					