

SPECIFICATION FOR APPROVAL

CERAMIC DISC CAPACITORS								
Customer:								
Capacitance: 4.7 nF	Tolerance: ±20 %		Issue No.					
Temp. Coef. Y5V	Q'ty of Sample: pcs		Issue Day. 13/07/2023					
Cust. P/N:	Part No. KV2K0472M-L516BD9		Rated Voltage : 2000 VDC					
Diagram of Dimensions : (Unit : mm)								
			<p>D: <u>9.0 max.</u> T: <u>4.5 max.</u> F: <u>5.0 ±0.8</u> L: <u>25.0 min.</u> d: <u>0.6 ±0.1</u> P: <u>4.0 max.</u></p>					
SPECIFICATION				Initial Test				
Frequency = 1K Hz Temperature = 25 °C				No	nF	Tanδ	I.R.	T.V.
1	Dissipation Factor (Tan δ): 5 % Max.			2.				
2	Insulation Resistance (IR) : 10,000 MΩ Min.			3.				
3	Dielectric Strength Test : DC 4,000 V			4.				
4	Case Insulation Test : DC 2,000 V			5.				
5	Temperature Characteristics: ΔC/C= +30%,-80% , +10°C~ +85°C			6.				
6	Lead Pull Test : 1.0 Kg 5 Seconds.			7.				
7	For further details please visit the following link of our website:			8.				
	Hi-Voltage 20230529.pdf			9.				
				10				
APPROVED BY CUSTOMER				REMARK :				
Your Confirmation : <input type="checkbox"/> Approval <input type="checkbox"/> Conditional Approval <input type="checkbox"/> Rejection (Please send a copy for our ref.)				Spec. Applied by EIA RS198 Test Instruments: (1). Capacitance: (a).CHEN HWA 1062 L.C.R.METER (1Khz). (b).ESI410 OR HP 4277 L.C.R.METER(1Mhz). (2). Dissipation Factor: as the Item (1). (3). Insulation Resistance: GENERAL RADIO 1864 MEGOHM METER. (4).Dielectric Strength: PHIHON PUNCTURE TESTER				
Inspected by		Checked by	吳美華	Approved by	蘇彥華			