

Digital Clamp Meter - True RMS
MS2003A



- Frequency: 2000Hz
- Relative
- MAX
- MIN
- Diode
- Continuity Check
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 4000
- Safety Rating: CAT III 600V
- Input Impedance $\geq 10M\Omega$
- Max Jaw Opening: 19mm
- Auto Power Off
- Data Hold
- Backlight
- Unit Display
- Battery: 1.5V AAA*2

MS2003A

Spec	Range	Accuracy
Resistance	400 Ω	$\pm(1.0\%+10)$
	4K Ω , 40K Ω , 400K Ω , 4M Ω	$\pm(0.8\%+5)$
	40M Ω	$\pm(2.0\%+10)$
DC Voltage	400mV	$\pm(0.7\%+5)$
	4V, 40V, 400V, 600V	$\pm(0.8\%+5)$
AC Voltage	4V, 40V, 400V, 600V	$\pm(1.0\%+5)$
AC Current	4A, 40A, 200A	$\pm(2.5\%+10)$
°C	-20 °C ~ 0 °C	± 4 °C
	0 °C ~ 400 °C	$\pm(2.0\%+3)$
	400 °C ~ 1000 °C	$\pm(3.0\%+3)$
°F	-4 °F ~ 50 °F	± 5 °F
	50 °F ~ 750 °F	$\pm(2.0\%+5)$
	750 °F ~ 1832 °F	$\pm(3.0\%+5)$
Capacitance	40nF	$\pm(4.0\%+25)$
	400nF ~ 400uF	$\pm(4.0\%+15)$
	4mF	$\pm(5.0\%+25)$
Frequency	10Hz ~ 10MHz	$\pm(0.5\%+2)$

Packaging Information	
Accessories	Carry bag, Test leads, Manual, Temperature probe, 1.5V*2 AAA Battery
Dimension	60mm*178mm*32mm
Weight	165g
Quantity	40
Color Box	75mm*55mm*195mm
Carton Box	400mm*315mm*395mm
SKU No.	MS2003ACBGLO
EAN Code	8435394788388

MGL Global Solutions (China) Company Limited

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China
 400-099-1987
 cs@mastech.cn



WeChat Official Account

www.mastech-group.com