



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D15*1.5mm
Magnetized direction	Through 1.5 mm direction
Weight	2.01 g/pc
Pull Force	1.5 KG $\pm$ 10%
Br	14.0 KGs
Coercive-Force Hcb	$\geq$ 10.5 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	48 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D15*3mm
Magnetized direction	Through 3 mm direction
Weight	4.02 g/pc
Pull Force	3 KG $\pm$ 10%
Br	14.0 KGs
Coercive-Force Hcb	$\geq$ 10.5 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	48 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D15*5mm
Magnetized direction	Through 5 mm direction
Weight	6.71 g/pc
Pull Force	5.3 KG $\pm$ 10%
Br	14.0 KGs
Coercive-Force Hcb	$\geq$ 10.5 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	48 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D25*6mm
Magnetized direction	Through 6 mm direction
Weight	22.38 g/pc
Pull Force	10 KG±10%
Br	14.0 KGs
Coercive-Force Hcb	≥10.5 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	48 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D25*25mm
Magnetized direction	Through 25mm direction
Weight	93.27 g/pc
Pull Force	44 KG $\pm$ 10%
Br	14.0 KGs
Coercive-Force Hcb	$\geq$ 10.5 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	48 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D30*15mm
Magnetized direction	Through 15 mm direction
Weight	38.7 g/pc
Pull Force	31 KG±10%
Br	14.0 KGs
Coercive-Force Hcb	≥10.5 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	48 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D40*20mm
Magnetized direction	Through 20 mm direction
Weight	191.01 g/pc
Pull Force	56 KG±10%
Br	14.0 KGs
Coercive-Force Hcb	≥10.5 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	48 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D50*25mm
Magnetized direction	Through 25 mm direction
Weight	373.06 g/pc
Pull Force	70 KG $\pm$ 10%
Br	14.0 KGs
Coercive-Force Hcb	$\geq$ 10.5 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	48 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N50
Coating	NI-CU-NI
Size	D55*25mm
Magnetized direction	Through 25 mm direction
Weight	451.41 g/pc
Pull Force	79 KG $\pm$ 10%
Br	14.0 KGs
Coercive-Force Hcb	$\geq$ 10.5 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	48 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民