	SC-350-12	SC-350-24
power	350W	350W
input voltage	110/220vac choose by switch.	
output voltage	12V 30A	24V 15A
Charger	Lead acid battery: 13.8V 1.5A	Lead acid battery: 27.6V 1.5A
	Lithium battery : 12.6V 1.5A	Lithium battery : 25.2V 1.5A
product size	215*115*50mm	
UPS function	AC input, DC output 30A 12V power supply to the power supply, while the other way 13.8V 1.5a for Lead acid battery charge, or 12.6v 1.5A for Lithium battery charge.  Automatic charge control, battery full automatic stop charging.  AC power failure, the output voltage automatically switches to the battery voltage output, 12V uninterrupted power supply. Zero switching time, the device does not stop, do not restart.  Battery voltage under voltage (less than 10.5V) automatically cut off the battery discharge output, under voltage protection to prevent battery over discharge battery voltage differential automatic processing function, effectively protect the battery Automatic switching control without manual intervention.	AC input, DC output 24v 15A power supply to the power supply, while the other way 27.6V 1.5a for Lead acid battery charge, or 25.2v 1.5A for Lithium battery charge.  Automatic charge control, battery full automatic stop charging.  AC power failure, the output voltage automatically switches to the battery voltage output, 24V uninterrupted power supply. Zero switching time, the device does not stop, do not restart.  Battery voltage under voltage (less than 22V) automatically cut off the battery discharge output, under voltage protection to prevent battery over discharge battery voltage differential automatic processing function, effectively protect the battery Automatic switching control without manual intervention.
four led indicator as follow	Green : AC working normal Red: backup power working yellow: backup Under-voltage blue: charging	