

ST Series Soldering Station



Features:

- Temperature locking.
- Beep alarm function available.
- MCU controlled temperature calibration.
- User-friendly menu enables system setting easier.
- Separate iron stand to save room and to make easier deposit.
- Buttons(1,2,3) for pre-setting or switching frequently used temperature.
- Low-voltage heater separated from power supply to keep soldering work safer.

Specification:

Product pictures			
Item No	ST-60	ST-80	ST-100
Voltage	AC(100V/110V/120V 220V/230V/240) 50/60Hz		
Power	60W	80W	100W
Temperature range	150°C~450°C	150°C~480°C	150°C~480°C
Temperature precision	±15°C	±10°C	±10°C
Temperature Stability	±2°C(in still air,no load)	±2°C(in still air,no load)	±2°C(in still air,no load)
The handle type	SP-60	SP-80	SP-100
Soldering tip type	T900-B	T900-B	T800-0.25I
Heat	High performance dual-core ceramic heater	High quality four-core wire heater	Sliver alloy heater
Package list	Main unit: 1unit Handle set : 1 PCS	Iron stand: 1 PCS AC cord: 1 PCS	Manual: 1 PCS Cleaning sponge: 1 PCS
Standard Packing	Inner box: 31.5x27x15.2(cm) N.W.: 2.09kg G.W.: 2.32kg Carton: 6PCS/Carton Size: 55.5x33x48(cm) N.W.: 14.4kg G.W.: 15.4kg	Inner box: 31.5x27x15.2(cm) N.W.: 2.58kg G.W.: 2.81kg Carton: 6PCS/Carton Size: 55.5x33x48(cm) N.W.: 16.9kg G.W.: 18.0kg	Inner box:31.5x27x15.2(cm) N.W.: 2.68kg G.W.: 2.95kg Carton: 6PCS/Carton Size: 55.5x33x48(cm) N.W.: 17.9kg G.W.: 19.0kg
Applicable	● Institutes ● Hobby	● Enterprises	● Education and practice ● Maintenance

Note: T800 series soldering tip details in page 18.
T900 series soldering tip details in page 25.