



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D3*10mm
Magnetized direction	Through 10mm direction
Weight	0.54 g/pc
Pull Force	1.6 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D4*5mm
Magnetized direction	Through 5mm direction
Weight	0.48 g/pc
Pull Force	1 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D6*1mm
Magnetized direction	Through 1mm direction
Weight	0.22 g/pc
Pull Force	0.32 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D7*5mm
Magnetized direction	Through 5mm direction
Weight	1.46 g/pc
Pull Force	1.8 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D8*10mm
Magnetized direction	Through 10mm direction
Weight	3.82 g/pc
Pull Force	4 KG±10%
Br	12.2 KGs
Coercive-Force Hcb	≥11.3 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	36 MGOe
Working Temperature	≤ 80℃





NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D13*1.5mm
Magnetized direction	Through 1.5mm direction
Weight	1.51 g/pc
Pull Force	1 KG±10%
Br	12.2 KGs
Coercive-Force Hcb	≥11.3 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	36 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D13*3mm
Magnetized direction	Through 3mm direction
Weight	3.03 g/pc
Pull Force	2 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D14*1.5mm
Magnetized direction	Through 1.5mm direction
Weight	1.75 g/pc
Pull Force	1 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D14*3mm
Magnetized direction	Through 3mm direction
Weight	3.5 g/pc
Pull Force	2 KG±10%
Br	12.2 KGs
Coercive-Force Hcb	≥11.3 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	36 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D20*1mm
Magnetized direction	Through 1mm direction
Weight	2.39 g/pc
Pull Force	1 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D20*2mm
Magnetized direction	Through 2mm direction
Weight	4.78 g/pc
Pull Force	2 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D25*6mm
Magnetized direction	Through 6mm direction
Weight	22.39 g/pc
Pull Force	8 KG±10%
Br	12.2 KGs
Coercive-Force Hcb	≥11.3 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	36 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D25*25mm
Magnetized direction	Through 25mm direction
Weight	93.27 g/pc
Pull Force	33 KG±10%
Br	12.2 KGs
Coercive-Force Hcb	≥11.3 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	36 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D30*15mm
Magnetized direction	Through 15mm direction
Weight	80.59 g/pc
Pull Force	24 KG $\pm$ 10%
Br	12.2 KGs
Coercive-Force Hcb	$\geq$ 11.3 KOe
Intrinsic Coercive Force Hcj	$\geq$ 12 KOe
(BH) Max	36 MGOe
Working Temperature	$\leq$ 80°C

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民



NINGBO BESTWAY M&E CO., LTD

Add: No. 225 Northern Section of Huancheng West Road, Ningbo, Zhejiang, China

Tel: 86-574-87504597 86-574-27788030 Fax: 86-574-87506697

E-mail: sales9@bwmagnet.com (Samantha) Website: www.bwmagnets.com

Technical Data Sheet

Specification	
Material	NdFeB
Grade	N38
Coating	NI-CU-NI
Size	D50*30mm
Magnetized direction	Through 30mm direction
Weight	447.68 g/pc
Pull Force	80 KG±10%
Br	12.2 KGs
Coercive-Force Hcb	≥11.3 KOe
Intrinsic Coercive Force Hcj	≥12 KOe
(BH) Max	36 MGOe
Working Temperature	≤ 80℃

宁波贝威机电有限公司
NINGBO BESTWAY M&E CO., LTD

吕新民