

Model	XG8080
Brand	sary
Product name	Magnetic lock
Size	80*80mm
Product Weight	0.24
Product material	zinc alloy
Power-on time	500ms
Working voltage	DC 12v
Working method	power on and open the door / power off, close the door and lock the door
Working humidity	-45°~65° (no freezing, no condensation)
Scope of application	all kinds of lattice cabinets, vending machines, filing cabinets, mobile phone cabinets, lockers, dressing rooms

Product Description

1. Compact structure design, free up more space for lockers 2. Built-in micro switch contact signal feedback, life expectancy up to 100,000 times 3. The lock body shell is made of 1.5MM zinc alloy material, which is sturdy and durable 4. The internal lock hook is made of powder metallurgy, which resists 50KG tensile force and will not damage and deform 5. Built-in high-strength spring compression bar, strengthen the elastic force of unlocking and opening the door 6. The SM2.54 connection terminal bears 20N pulling force without falling off 7. Different lock hooks are suitable for different locker designs, and customized services can be provided



Micro-switch contact signal feedback structure, lock that signal line conduction, unlock signal line open



Feedback line

Power Cord



SM2.54 connector wire

High-strength metal shackle.
It can resist 50KG pulling force without damage and unlocking.



Emergency manual switch device



Thickened zinc alloy shell; rust and corrosion resistant
Thicken

Spring ejector design
Strengthen the elasticity of unlocking and opening the door