

MS2015A

JAW SIZE

Φ40mm/1.6"

VOLTAGE AC 750V
DC 1000V

CURRENT

AC 1000A

\bar{V} \bar{A} Ω

$\frac{1}{f}$ Hz% AUTO

Apo REL \rightarrow

MAX MIN \square

\odot \square \rightarrow

TRMS NCV



MS2015C

JAW SIZE

Φ40mm/1.6"

VOLTAGE AC 750V
DC 1000V

CURRENT

AC 1000A

\bar{V} \bar{A} Ω

$\frac{1}{f}$ Hz% AUTO

Apo REL \rightarrow

MAX MIN \square

\odot \square \rightarrow

TRMS NCV



Specifications

MS2015A MS2015C

Specifications	Range	Accuracy	
DC Voltage	60mV/600mV/6V/60V/600V	±(0.5%+5)	
	660mV		±(0.8%+2)
	6.6V/66V/660V		±(0.7%+2)
	1000V	±(0.8%+2)	±(0.8%+2)
AC Voltage	60mV/600mV/6V/60V/600V	±(0.8%+3)	
	6.6V/66V/660V		±(0.8%+3)
	750V	±(1.0%+4)	±(1.0%+4)
AC Current	60A/600A/1000A	±(2.0%+6)	
	66A/660A/1000A		±(2.5%+6)
Resistance	600Ω/6kΩ/60kΩ/600kΩ	±(0.8%+3)	
	6MΩ/60MΩ		±(1.2%+3)
	660Ω/6.6kΩ/66kΩ/660kΩ		±(0.8%+3)
	6.6MΩ/66MΩ		±(1.2%+3)
Capacitance	10nF/100nF/1000nF/10μF/ 100μF/1000μF/10mF/100mF	±(4.0%+5)	
	6.6nF/66nF/660nF/6.6μF/ 66μF/660μF/6.6mF/66mF		±(4.0%+5)
Frequency (From Clamp)	0~10KHz	±(1.5%+5)	±(1.5%+5)
Frequency (AC Voltage)	0~10KHz	±(1.5%+5)	±(1.5%+5)
Logic Frequency	0~10MHz	±(0.5%+2)	
	66Hz~66MHz		±(0.5%+2)
Duty Cycle	5.0%~95%	±3.0%	±3.0%
Temperature	-20°C~1000°C/-4°F~1832°F		±(2%+2)

Features			
Display	counts	6000	6600
Jaw Opening		Φ40mm/1.6"	Φ40mm/1.6"
Auto Ranging	Auto & Manual	●	●
APO	Auto Power Off	●	●
REL	Relative Measurement	●	●
Diode	2.7V	●	●
Continuity Buzzer	<50Ω	●	●
MAX/MIN		●	●
Data Hold		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●
Work Light		●	●
True RMS	True Root Mean Square	●	●
NCV	Non-Contact Voltage Detector	●	●
Dual Display			●
Bar Graph	Segments Bar Graph		●
General			
Power Supply	1×9V 6F22 Battery		
Product Size	238mm×92mm×50mm/9.37"×3.6"×1.9"		
Product Weight	390g/0.86lb		
Safety Rating	CE CAT III 1000V RoHS		

● Feature Difference