

Digital Multimeter - True RMS

MS850B



- Buzzer / Continuity Check / Diode
- MAX / MIN / True RMS / REL
- Non-Contact Voltage (NCV) Detection / Live Wire (Live) Recognition
- Max Display: 2000
- CAT III 600V
- Input Impedance $\geq 10M\Omega$
- Auto Power Off / Data Hold
- Backlight / Flashlight
- Battery: 1.5V AAA*2

MS850B

Spec	Range	Accuracy	Spec	Range	Accuracy
Resistance	200 Ω , 2K Ω , 20K Ω , 200K Ω , 2M Ω	$\pm(1.0\%+5)$	AC Current	200 μ A, 2000 μ A, 20mA	$\pm(1.8\%+5)$
	20M Ω	$\pm(1.2\%+8)$		200mA	$\pm(2.5\%+5)$
DC Voltage	20mV	$\pm(1.0\%+5)$	°C	2A, 10A	$\pm(3.0\%+5)$
	200mV, 2V	$\pm(0.5\%+3)$		-20 °C ~ 0 °C	$\pm 4^{\circ}\text{C}$
	20V, 200V	$\pm(0.8\%+3)$	0 °C ~ 400 °C	$\pm(2.0\%+3)$	
	600V	$\pm(0.8\%+5)$	400 °C ~ 1000 °C	$\pm(3.0\%+3)$	
AC Voltage	20mV, 200mV, 2V, 20V, 200V, 600V	$\pm(1.0\%+10)$	°F	-4 °F ~ 50 °F	$\pm 5^{\circ}\text{F}$
	200 μ A, 2000 μ A, 20mA	$\pm(1.0\%+5)$		50 °F ~ 750 °F	$\pm(2.0\%+5)$
DC Current	200mA	$\pm(2.0\%+5)$	Battery Test	750 °F ~ 1832 °F	$\pm(3.0\%+5)$
	2A, 10A	$\pm(3.0\%+5)$		1.5V, 3V, 9V	-

Packaging Information	
Accessories	Test leads, Manual, Temperature probe, 1.5V*2 AAA Battery
Dimension	235mm*96mm*46mm
Weight	284g
Quantity	40
Color Box	112mm*54mm*155mm
Carton Box	495mm*310mm*465mm
SKU No.	MS850BCBGLO
EAN Code	8435394788524

MGL Global Solutions (China) Company Limited

R72, Puxing East Road, Qingxi, Dongguan, Guangdong, China
400-099-1987
cs@mastech.cn



WeChat Official Account

www.mastech-group.com