

RACK-200

2U Height Full Size Industrial PC Chassis



RACK-200G



RACK-200W Top View

Specifications

- ◆ 2U height 19" Rack mounting chassis
- ◆ Plastic front panel
- ◆ Drive Bays: 2 x 3.5" FDD
- ◆ One 8cm cooling fan with filter
- ◆ AT type KBD connector on front panel
- ◆ Supports backplane: BP-5SD, PCI-5SD3, PCI-5SD5-R2, PCI-5SD6, PCI-6SR, IP-5SD3, IP-5SD5
- ◆ Supports power supply: PS/2 size AT/ATX power supply (ACE-93x/92x/916V/940AP, ACE-828 and ACE-832 series, ACE-840A, ACE-840AP-S, ACE-850AP)
- ◆ Vibration: 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock: 10G acceleration peak to peak (11ms)
- ◆ Colors: Industrial Green (PANTONE 417C) or White (PANTONE 413C)
- ◆ Dimensions: 431(W)x88(H)x454(D)mm; (17"x3.5"x17.9")
- ◆ Net/GW (kg): 9/10

Ordering Information

- RACK-200 /ACE-920A
2U rackmount chassis with ACE-920A power supply
- Color Code : G: Green W: White

RACK-210

2U Height Full Size Industrial PC Chassis



RACK-210G



RACK-210W Top View

Specifications

- ◆ 2U height 19" Rack mounting chassis
- ◆ Plastic front panel
- ◆ Drive Bays : 1 x 5.25" Drive, 1 x 3.5" FDD, 2 x 3.5" HDD (Internal)
- ◆ One 8cm cooling fan with filter
- ◆ AT type KBD connector on front panel
- ◆ Supports backplane: BP-5SD, PCI-5SD3, PCI-5SD5-R2, PCI-5SD6, PCI-6SR, IP-5SD3, IP-5SD5
- ◆ Supports power supply: PS/2 size AT/ATX power supply (ACE-93x/92x/916V/940AP, ACE-828 and ACE-832 series, ACE-840A, ACE-840AP-S, ACE-850AP)
- ◆ Vibration: 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock: 10G acceleration peak to peak (11ms)
- ◆ Colors: Industrial Green (PANTONE 417C) or White (PANTONE 413C)
- ◆ Dimensions: 431(W)x88(H)x477(D)mm; (17"x3.5"x18.8")
- ◆ Net/GW (kg): 8/11

Ordering Information


- RACK-210 /ACE-920A
2U rackmount chassis with ACE-920A power supply
- Color Code : G: Green W: White

RACK-260

2U Height ATX Main Board Industrial PC Chassis



RACK-260



PCIAGPR-03H

Specifications

- ◆ 2U Height 19" Rack mounting chassis
- ◆ Drive bays: 1 x 5.25" CD-ROM, 1 x 3.5" FDD, 2 x 3.5" HDD (Internal)
- ◆ Two 8cm cooling fan
- ◆ Support standard ATX and micro ATX Main Board
- ◆ Support three half size PCI add-on cards
- ◆ Support Power Supply: standard equipped with ACE-832A Power Supply
- ◆ Optional PS/2 size AT/ATX power supply
- ◆ Vibration: 5~17Hz, 0.1" double amplitude displacement
17~640 Hz, 1.5G acceleration part to part
- ◆ Shock: 10G acceleration part to part (11ms)
- ◆ Operating temperature: 0~50°C
- ◆ Color: Black (PANTONE Black C) , White (PANTONE 413C)
- ◆ Dimension: 431mm(W) x 88.5mm(H) x 480mm(D)
- ◆ Net/GW (kg): 10/13

Ordering Information

- RACK - 260 / ACE - 832A
2U Height Main board Industrial PC Chassis with ACE-832A power supply
- Color Code B=Black W=White

Option: PCIR-03 Three PCI slot riser card
PCIAGPR-03H One PCI slot and one AGP slot riser card

RACK-220A

2U Chassis



RACK-220AB



RACK-220AW Top View

Specifications

- ◆ 2U height 19" Rack mounting chassis
- ◆ Designed with fan fault detecting system
- ◆ Front panel locking door system protects disk access and power on/off switches
- ◆ Drive Bays: 1 x 3.5" FDD; 1 x 5.25" Drive; 1 x 3.5" HDD (Internal)
- ◆ One 8cm cooling fan with removable filter
- ◆ Optional backplane: BP-5SD, PCI-5SD3, PCI-5SD5-R2, PCI-5SD6, PCI-6SR, IP-5SD3, IP-5SD5
- ◆ Supports power supply: PS/2 size AT/ATX power supply (ACE-93x/92x/916V/940AP, ACE-828 and ACE-832 series, ACE-840A, ACE-840AP-S, ACE-850AP)
- ◆ Vibration: 5 ~ 17Hz, 0.1" double amplitude displacement
17 ~ 640Hz, 1.5G acceleration peak to peak
- ◆ Shock: 10G acceleration peak to peak (11ms)
- ◆ Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- ◆ Dimensions: 431(W) x 88(H) x 473(D)mm; (17" x 3.5" x 18.6")
- ◆ Net/GW (kg): 9/12

Ordering Information

- RACK-220A / ACE-920A
2U rackmount chassis with ACE-920A power supply
- Color CODE: B=Black; W=White =Power supply module