東莞市智旭電子有限公司
JYH HSU (JEC) ELECTRONICS LTD.,

文件编号：P015
版　　本：0
制定日期：2020.08.20

承 认 书
SPECIFICATION FOR APPROVAL

客 户 名 称
CUSTOMER _____

品　　名
PART NAME capacitor

客户料号
Customer Part No: _____

承 認 規 格
APPROVE ITEM please refer to the list

供应商料号
Part Number please refer to the list

日　　期
DATE **2024.9.10**

客户承认 Customer approval	供应商承认 Supplier admit that 东莞市智旭电子有限公司 品保部

台湾:智旭电子有限公司
JYH HSU(JEC) ELECTRONICSLTD
台湾台中大里市仁路 222 巷 64 号
TEL：886-422752703
FAX：886-422752236
E-mail: vinkyyuan@gmail.com

广东：智旭电子有限公司
JYH HSU(JEC) ELECTRONICS LTD
东莞市道窖镇蔡白村道厚路律冲桥头旁
TEL：0769-88313601　88313602
FAX：0769-88313603
E-mail: vinkyyuan@gmail.com

Product List

NO.	Model	Capacity (uf)	Voltage (V)	Tolerance (%)	Size D*L (mm)	operating temperature	P/N
1	3.5uF 450VAC	3.5	450	±5	30*57	-25℃~85℃	355J450V30*57
2	8uF 450VAC	8	450	±5	34*65	-25℃~85℃	805J450V34*65
3	25uF 450VAC	25	450	±5	40*70	-25℃~85℃	256J450V40*70
4	2.5uF 450VAC	2.5	450	±5	30*57	-25℃~85℃	255J450V30*57
5	12uF 450VAC	12	450	±5	40*70	-25℃~85℃	126J450V40*70
6	30uF 450VAC	30	450	±5	45*95	-25℃~85℃	306J450V45*95
7	45uF 450VAC	45	450	±5	45*95	-25℃~85℃	456J450V45*95
8	60uF 450VAC	60	450	±5	50*106	-25℃~85℃	606J450V50*106
9	14uF 450VAC	14	450	±5	40*70	-25℃~85℃	146J450V40*70
10	6uF 450VAC	6	450	±5	34*65	-25℃~85℃	605J450V34*65
11	16uF 450VAC	16	450	±5	40*70	-25℃~85℃	166J450V40*70
12	10uF 450VAC	10	450	±5	34*65	-25℃~85℃	106J450V34*65
13	4uF 450VAC	4	450	±5	30*57	-25℃~85℃	405J450V30*57

CBB60 Capacitor Specifications

This capacitor uses metallized film with thickened edges as electrodes and dielectrics. The components inside are wrapped with flame-retardant epoxy resin. The appearance of this product is cylindrical, with ABS or PBT plastic shell. It has good stability and moisture resistance.

Technical Specifications

·Implementation standard: GB/T3667-2005

Use requirements:

·Altitude: <2000m

·Residual voltage when put into use: not more than 10% of the rated voltage

·Maximum allowable voltage: not more than 1.1 times the rated voltage

·Maximum allowable current: not more than 1.3 times the rated current Specifications and dimensions (mm)

Product model: CBB60

Product appearance: cylindrical

Dielectric material: metallized film

Adjustment method: fixed

Lead type: double plug-in

Withstand voltage: 450 (V)